



MIX Multi-Channel Signal Isolator and Converter

Model: **MIX/4X4-20mA/4X4-20mA/12-42DC [DIN]**

Featuring a very narrow installation footprint, the MIX miniMoore™ Signal Isolator, Converter, Splitter and Booster combine multiple analog signal channels in a rugged, easy-to-install signal conditioner.

Product Details

Input	4X4-20mA
Output	4X4-20mA
Power	12-42DC
Input Description	4-channels, fixed for 4-20mA
Output Description	4-channels, fixed for 4-20mA
Power Description	12-42DC, Output loop powered
Housing Description	Universal DIN-style housing, 32mm G-type and 35mm Top Hat
HART Signal Pass-through Capability	No
For use in Safety Instrumented Systems (SIS)	No
Number of Inputs	1, 2, 3, 4
Input Type	4-20mA
Number of Outputs	1, 2, 3, 4
Device Power	2-Wire, Loop Powered
Integral Display	No
Alarm/Relay Output	No
Configuration/Setup	Fixed Input/Output
Enhanced RFI/EMI Immunity	No
Housing/Enclosure	DIN Rail Enclosure
2" Pipe Mount Bracket	No
Hazardous Area Certifications	UL Approved, CSA General Location, Non-Incendive/Div. 2
RoHS Compliant	Yes