



T2X Non-Isolated PC-Programmable Temperature Transmitter

Model: **T2X/PRG/4-20mA/8-42DC [LH2NSP]**

Moore Industries' Cost Competitive PC-Programmable T2X RTD Temperature Transmitters combine smart digital technology with advanced analog operation to deliver superior reliability, accuracy and ease of use.

Product Details

Input	PRG
Output	4-20mA
Power	8-42DC
Input Description	Programmable Input for RTD, Potentiometer and Ohms
Output Description	4-20mA
Power Description	2-Wire, Output Loop Powered
Housing Description	Aluminum Explosion-proof/Flameproof connection head with two entry ports
Output/Digital Communications	4-20mA Only
For use in Safety Instrumented Systems (SIS)	No
Device Power	2-Wire, Loop Powered
Input	Configurable: RTD, Ohms, Potentiometer
Integral Display	No
Alarm/Relay Output	No
Intrinsically-Safe Input Connections	No
Configuration/Setup	PC Configurable, USB Cable
Enhanced RFI/EMI Immunity	No
Isolation	Non-isolated
Housing/Enclosure	Explosion Proof/Flameproof IP66 Field Mount Enclosure
2" Pipe Mount Bracket	Yes
Field Enclosure Conduit Connection	Standard (NPT)
Hazardous Area Certifications	Non-Incendive/Div. 2, Zone 2, Explosion Proof, Flameproof
RoHS Compliant	In Process